P-Ch 20V Fast Switching MOSFETs

★ Super Low Gate Charge
★ Green Device Available
★ Excellent CdV/dt effect decline
★ Advanced high cell density Trench technology

Product Summary

Green


BVDSS	RDSON	ID
-20V	23mΩ	-5.0A

Description

The XR2311L is the high cell density trenched P-ch MOSFETs, which provides excellent RDSON and gate charge for most of the synchronous buck converter applications
The XR2311L meets the RoHS and Green Product requirements with full function reliability approved.

SOT 23-3L Pin Configurations





Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	±12	V
I_D@T_A=25℃	Continuous Drain Current, V_{GS} @ -4.5V[1]	-5.0	A
I_D@T_A=70℃	Continuous Drain Current, V_{GS} @ -4.5V[1]	-3.0	A
I_{DM}	Pulsed Drain Current[2]	-16	A
P_D@T_A=25℃	Total Power Dissipation[3]	1.31	W
P_D@T_A=70℃	Total Power Dissipation[3]	0.84	W
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-Ambient [1]	---	125	℃/W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient [1] (t ≤10s)	---	---	℃/W

Electrical Characteristics (T_J=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D= -250μA	-20	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}= -20V, V_{GS}=0V,	-	-	-1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS}=0V, V_{GS}= ±12V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D= -250μA	-0.4	-0.7	-1.0	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note2	V_{GS}= -4.5V, I_D= -4.1A	-	23	28	mΩ
		V_{GS}= -2.5V, I_D= -3A	-	27	35	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}= -10V, V_{GS}=0V, f=1.0MHz	-	830	-	pF
C_{oss}	Output Capacitance		-	132	-	pF
C_{rss}	Reverse Transfer Capacitance		-	85	-	pF
Q_g	Total Gate Charge	V_{DS}= -10V, I_D= -2A, V_{GS}= -4.5V	-	8.8	-	nC
Q_{gs}	Gate-Source Charge		-	1.4	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	1.9	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD}= -10V, I_D= -3.3A, R_G= 1Ω, V_{GEN}= -4.5V	-	10	-	ns
t_r	Turn-on Rise Time		-	32	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	50	-	ns
t_f	Turn-off Fall Time		-	51	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	-5.0	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	-16	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS}=0V, I_S= -4.1A	-	-	-1.2	V

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width≤300μs, Duty Cycle≤2%

Typical Performance Characteristics

Figure1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature






Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Package Mechanical Data-SOT-23-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°